



| Type | Displacement cm ³ /rev | Flow | | Pressure P _{nom} bar | max Speed n rpm | Dimension | | | | | | | | |
|---------------|--------------------------------------|----------------------|---------------------|-------------------------------------|-----------------------|-----------|---------|-------|----|-------|--------|----|-------|--|
| | | at 1500 rpm l/min | at max rpm l/min | | | A mm | B mm | Inlet | | | Outlet | | | |
| | | | | | | E | F | d | E | F | d | | | |
| 20A(C)4,5X022 | 4,5 | 6,14 | 14,33 | 250 | 3500 | 41,4 | 79,6 | 40 | 15 | M6-6H | 35 | 15 | M6-6H | |
| 20A(C)6,3X022 | 6,3 | 8,69 | 20,29 | 250 | 3500 | 42,6 | 82,6 | | | | | | | |
| 20A(C)8,2X022 | 8,2 | 11,32 | 26,40 | 250 | 3500 | 44,7 | 85,5 | | | | | | | |
| 20A(C)10X022 | 10 | 13,95 | 32,55 | 250 | 3500 | 49,1 | 88,6 | | 20 | | | | | |
| 20A(C)11X022 | 11,3 | 15,76 | 36,78 | 250 | 3500 | 49,1 | 90,7 | | | | | | | |
| 20A(C)12X022 | 12 | 16,92 | 39,48 | 250 | 3500 | 49,1 | 91,9 | | 20 | | | | | |
| 20A(C)14X022 | 14 | 19,95 | 46,55 | 250 | 3500 | 49,1 | 95 | | | | | | | |
| 20A(C)15X022 | 15 | 21,60 | 36,00 | 250 | 2500 | 49,1 | 96,5 | | | | | | | |
| 20A(C)16X022 | 16 | 23,04 | 38,40 | 250 | 2500 | 49,1 | 98,2 | | | | | | | |
| 20A(C)19X022 | 19 | 27,36 | 45,60 | 200 | 2500 | 49,1 | 103,1 | | | | | | | |
| 20A(C)22X022 | 22 | 31,68 | 42,24 | 180 | 2000 | 56,6 | 108,1 | | | | | | | |
| 20A(C)25X022 | 25 | 36,00 | 48,00 | 160 | 2000 | 58,8 | 113 | | | | | | | |