


SAE J475 (ISO R725)



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension													
		at 1500 rpm l/min	at max rpm l/min			Inlet			Outlet										
						A mm	B mm	M	G	U	M	G	U						
20A(C)4,5X085...	4,5	6,14	14,33	250	3500	42	79,6	M20x1,5	G1/2	1 1/16"-12UNF	M16x1,5	G1/2	7/8"-14UNF						
20A(C)6,3X085...	6,3	8,69	20,29	250	3500	43,6	82,6												
20A(C)8,2X085...	8,2	11,32	26,40	250	3500	45	85,6												
20A(C)10X085...	10	13,95	32,55	250	3500	46,6	88,7												
20A(C)11X085...	11,3	15,76	36,78	250	3500	47,6	90,7												
20A(C)12X085...	12	16,92	39,48	250	3500	48,2	91,9												
20A(C)14X085...	14	19,95	46,55	250	3500	49,6	95												
20A(C)15X085...	15	21,60	36,00	250	2500	50,6	96,5												
20A(C)16X085...	16	23,04	38,40	250	2500	51,6	98,2												
20A(C)19X085...	19	27,36	45,60	200	2500	53,6	103,1												
20A(C)22X085...	22	31,68	42,24	180	2000	56,6	108,1	M20x1,5	G3/4	1 1/16"-12	M16x1,5	G1/2	7/8"-14UNF						
20A(C)25X085...	25	36,00	48,00	160	2000	58,8	113												
20A(C)14X085H...	14	20,16	47,04	250	3500	54,8	105,7	M20x1,5	G3/4	1 1/16"-12UNF	M16x1,5	G1/2	7/8"-14UNF						
20A(C)15X085H...	15	21,60	43,20	250	3000	55,6	106,8												
20A(C)16X085H...	16	23,04	46,08	250	3000	56,5	108,4												
20A(C)17,3X085H...	17,3	24,91	49,82	230	3000	57,6	110,5												
20A(C)18,2X085H...	18,2	26,21	52,42	210	3000	58,4	112,1												
20A(C)19X085H...	19	27,36	54,72	200	3000	59	113,4												
20A(C)22X085H...	22	31,68	52,80	180	2500	61,5	118,4												
20A(C)25X085H...	25	36,00	60,00	160	2500	63,9	123,3												
20A(C)28X085H...	28	40,32	67,20	130	2500	66,4	128,1							M27x2	G1	1 5/16"-12	M20x1,5	G3/4	1 1/16"-12
20A(C)32X085H...	32	46,08	61,44	120	2000	69,6	134,4												
20A(C)36X085H...	36	51,84	69,12	100	2000	72,8	141												