


SAE J475 (ISO R725)



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension												
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet							
								M	G	U	M	G	U					
20A(C)4,5X111...	4,5	6,14	14,33	250	3500	42,5	87,2	M20x1,5	G1/2	1 1/16"-12UNF	M16x1,5	G1/2	7/8"-14UNF					
20A(C)6,3X111...	6,3	8,69	20,29	250	3500	44	90,2											
20A(C)8,2X111...	8,2	11,32	26,40	250	3500	45,5	93,1											
20A(C)10X111...	10	13,95	32,55	250	3500	47	96,2		G3/4									
20A(C)11X111...	11,3	15,76	36,78	250	3500	48	98,2											
20A(C)12X111...	12	16,92	39,48	250	3500	48,6	99,5		G3/4									
20A(C)14X111...	14	19,95	46,55	250	3500	50	102,6											
20A(C)15X111...	15	21,60	36,00	250	2500	51	104,1		M20x1,5									
20A(C)16X111...	16	23,04	38,40	250	2500	52	105,8											
20A(C)19X111...	19	27,36	45,60	200	2500	54	110,7		M20x1,5									
20A(C)22X111...	22	31,68	42,24	180	2000	57	115,7											
20A(C)25X111...	25	36,00	48,00	160	2000	59,2	120,6											