



Type	Displacement cm <sup>3</sup> /rev	Flow		Pressure P <sub>nom</sub> bar	max Speed n rpm	Dimension							
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet		
								E	F	d	E	F	d
20A(C)4,5X187	4,5	6,14	14,33	250	3500	37,3	82,3	40	15	M6-6H	35	15	M6-6H
20A(C)6,3X187	6,3	8,69	20,29	250	3500	38,6	85,2						
20A(C)8,2X187	8,2	11,32	26,40	250	3500	40,6	85,2						
20A(C)10X187	10	13,95	32,55	250	3500	45	94,1						
20A(C)11X187	11,3	15,76	36,78	250	3500	45	96,2						
20A(C)12X187	12	16,92	39,48	250	3500	45	97,5						
20A(C)14X187	14	19,95	46,55	250	3500	45	100,6						
20A(C)15X187	15	21,60	36,00	250	2500	45	102,1						
20A(C)16X187	16	23,04	38,40	250	2500	45	103,8						
20A(C)19X187	19	27,36	45,60	200	2500	45	108,7						
20A(C)22X187	22	31,68	42,24	180	2000	52,5	113,7						
20A(C)25X187	25	36,00	48,00	160	2000	57,2	118,6						