



| Type | Displacement cm ³ /rev | Flow | | Pressure P _{nom} bar | max Speed n rpm | Dimension | | | | | | | |
|----------------|--------------------------------------|----------------------|---------------------|-------------------------------------|-----------------------|-----------|---------|---------|---------|---------|---------|---------|---------|
| | | at 1500 rpm l/min | at max rpm l/min | | | A mm | B mm | Inlet | | | Outlet | | |
| | | | | | | | | E mm | F mm | d mm | E mm | F mm | d mm |
| 20A(C)4,5X429V | 4,5 | 6,14 | 14,33 | 250 | 3500 | 42,5 | 87,2 | 30,2 | 13,1 | M6-6H | 30,2 | 13,1 | M6-6H |
| 20A(C)6,3X429V | 6,3 | 8,69 | 20,29 | 250 | 3500 | 42,5 | 87,2 | | | | | | |
| 20A(C)8,2X429V | 8,2 | 11,32 | 26,40 | 250 | 3500 | 42,5 | 87,2 | | | | | | |
| 20A(C)10X429V | 10 | 13,95 | 32,55 | 250 | 3500 | 47 | 96,2 | 39,7 | 19 | M8-6H | | | |
| 20A(C)11X429V | 11,3 | 15,76 | 36,78 | 250 | 3500 | 48 | 98,3 | | | | | | |
| 20A(C)12X429V | 12 | 16,92 | 39,48 | 250 | 3500 | 48,7 | 99,5 | | | | | | |
| 20A(C)14X429V | 14 | 19,95 | 46,55 | 250 | 3500 | 50,2 | 102,5 | M8-6H | 14,2 | M6-6H | | | |
| 20A(C)15X429V | 15 | 21,60 | 36,00 | 250 | 2500 | 51 | 104,1 | | | | | | |
| 20A(C)16X429V | 16 | 23,04 | 38,40 | 250 | 2500 | 51,8 | 105,8 | | | | | | |
| 20A(C)19X429V | 19 | 27,36 | 45,60 | 200 | 2500 | 54 | 110,7 | M8 | 19 | M8 | | | |
| 20A(C)22X429V | 22 | 31,68 | 42,24 | 180 | 2000 | 56,5 | 115,7 | | | | | | |
| 20A(C)25X429V | 25 | 36,00 | 48,00 | 160 | 2000 | 58,8 | 120,6 | | | | | | |