



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension								
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet			
						E	F	d	E	F	d			
20A(C)4,5X087	4,5	6,14	14,33	250	3500	37,3	75,1	40	15	M6-6H	35	15	M6-6H	
20A(C)6,3X087	6,3	8,69	20,29	250	3500	38,6	78							
20A(C)8,2X087	8,2	11,32	26,40	250	3500	40,6	78							
20A(C)10X087	10	13,95	32,55	250	3500	45	87							
20A(C)11X087	11,3	15,76	36,78	250	3500	45	89,1							
20A(C)12X087	12	16,92	39,48	250	3500	45	90,3							
20A(C)14X087	14	19,95	46,55	250	3500	45	93,4							
20A(C)15X087	15	21,60	36,00	250	2500	45	94,9							
20A(C)16X087	16	23,04	38,40	250	2500	45	96,5							
20A(C)19X087	19	27,36	45,60	200	2500	45	101,5							
20A(C)22X087	22	31,68	42,24	180	2000	52,5	106,5							
20A(C)25X087	25	36,00	48,00	160	2000	57,2	111,4							