



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension							
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet		
								M	G	U	M	G	U
20A(C)4,5X114...	4,5	6,14	14,33	250	3500	42,5	80	M18x1,5	G1/2		M14x1,5		
20A(C)6,3X114...	6,3	8,69	20,29	250	3500	42,5	80	M18x1,5	G1/2		M14x1,5		
20A(C)8,2X114...	8,2	11,32	26,40	250	3500	42,5	80	M18x1,5	G1/2		M14x1,5		
20A(C)10X114...	10	13,95	32,55	250	3500	47	89	M22x1,5	G1/2		M18x1,5		
20A(C)11X114...	11,3	15,76	36,78	250	3500	48,6	91,1	M22x1,5	G1/2		M18x1,5		
20A(C)12X114...	12	16,92	39,48	250	3500	49	92,3	M22x1,5	G1/2		M18x1,5		
20A(C)14X114...	14	19,95	46,55	250	3500	49	95,4	M27x2	G3/4		M18x1,5		
20A(C)15X114...	15	21,60	36,00	250	2500	49,5	96,9	M27x2	G3/4		M18x1,5		
20A(C)16X114...	16	23,04	38,40	250	2500	52	98,6	M27x2	G3/4		M18x1,5		
20A(C)19X114...	19	27,36	45,60	200	2500	53	103,5	M27x2	G3/4		M18x1,5		
20A(C)22X114...	22	31,68	42,24	180	2000	57	108,5	M27x2	G3/4		M18x1,5		
20A(C)25X114...	25	36,00	48,00	160	2000	59,2	113,4	M27x2	G3/4		M18x1,5		