



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension							
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet		
								E	F	d	E	F	d
20A(C)4,5X207	4,5	6,14	14,33	250	3500	42,5	80						
20A(C)6,3X207	6,3	8,69	20,29	250	3500	42,5	80	30,2	13,1	1/4-20UNC		13,1	
20A(C)8,2X207	8,2	11,32	26,40	250	3500	42,5	80						
20A(C)10X207	10	13,95	32,55	250	3500	47	89						
20A(C)11X207	11,3	15,76	36,78	250	3500	48	91,1						
20A(C)12X207	12	16,92	39,48	250	3500	48,6	92,3						
20A(C)14X207	14	19,95	46,55	250	3500	50	95,4						
20A(C)15X207	15	21,60	36,00	250	2500	51	96,9	39,7			30,2		
20A(C)16X207	16	23,04	38,40	250	2500	52	98,6		19				
20A(C)19X207	19	27,36	45,60	200	2500	54	103,5			5/16"-18UNC		14,2	
20A(C)22X207	22	31,68	42,24	180	2000	57	108,5						
20A(C)25X207	25	36,00	48,00	160	2000	59,2	113,4				39,7	19	5/16"