



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension								
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet			
						E	F	d	E	F	d			
20A(C)4,5X210	4,5	6,14	14,33	250	3500	41,4	86,8	40	20	M6-6H	35	15	M6-6H	
20A(C)6,3X210	6,3	8,69	20,29	250	3500	42,6	89,8							
20A(C)8,2X210	8,2	11,32	26,40	250	3500	44,7	92,7							
20A(C)10X210	10	13,95	32,55	250	3500	49,1	95,7							
20A(C)11X210	11,3	15,76	36,78	250	3500	49,1	97,8							
20A(C)12X210	12	16,92	39,48	250	3500	49,1	99,1							
20A(C)14X210	14	19,95	46,55	250	3500	49,1	102,2							
20A(C)15X210	15	21,60	36,00	250	2500	49,1	103,7							
20A(C)16X210	16	23,04	38,40	250	2500	49,1	105,3							
20A(C)19X210	19	27,36	45,60	200	2500	49,1	110,3							
20A(C)22X210	22	31,68	42,24	180	2000	56,6	115,3							
20A(C)25X210	25	36,00	48,00	160	2000	58,8	120,2							