



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension								
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet			
						E	F	d	E	F	d			
20A(C)4,5X223	4,5	6,14	14,33	250	3500	42,5	80							
20A(C)6,3X223	6,3	8,69	20,29	250	3500	42,5	80	30,2	13,1	M6-6H		13,1		
20A(C)8,2X223	8,2	11,32	26,40	250	3500	42,5	80							
20A(C)10X223	10	13,95	32,55	250	3500	47	89							
20A(C)11X223	11,3	15,76	36,78	250	3500	48	91,1							
20A(C)12X223	12	16,92	39,48	250	3500	48,6	92,3							
20A(C)14X223	14	19,95	46,55	250	3500	50	95,4							
20A(C)15X223	15	21,60	36,00	250	2500	51	96,9	39,7	19	M8-6H	30,2	14,2	M6-6H	
20A(C)16X223	16	23,04	38,40	250	2500	52	98,6							
20A(C)19X223	19	27,36	45,60	200	2500	54	103,5							
20A(C)22X223	22	31,68	42,24	180	2000	57	108,5							
20A(C)25X223	25	36,00	48,00	160	2000	59,2	113,4				39,7	19	M8	