



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension								
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet			
						E	F	d	E	F	d			
20A(C)4,5X341	4,5	6,14	14,33	250	3500	41,8	87,2	40	15	M6-6H	35	15	M6-6H	
20A(C)6,3X341	6,3	8,69	20,29	250	3500	43	90,2							
20A(C)8,2X341	8,2	11,32	26,40	250	3500	45,1	93,1							
20A(C)10X341	10	13,95	32,55	250	3500	49,5	96,2							
20A(C)11X341	11,3	15,76	36,78	250	3500	49,5	98,2							
20A(C)12X341	12	16,92	39,48	250	3500	49,5	99,5							
20A(C)14X341	14	19,95	46,55	250	3500	49,5	102,6							
20A(C)15X341	15	21,60	36,00	250	2500	49,5	104,1							
20A(C)16X341	16	23,04	38,40	250	2500	49,5	105,8							
20A(C)19X341	19	27,36	45,60	200	2500	49,5	110,7							
20A(C)22X341	22	31,68	42,24	180	2000	57	115,7							
20A(C)25X341	25	36,00	48,00	160	2000	59,2	120,6							