



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension								
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet			
						E	F	d	E	F	d			
20A(C)4,5X586B	4,5	6,14	14,33	250	3500	40,5	85,2	40	20	M6-6H	35	15	M6-6H	
20A(C)6,3X586B	6,3	8,69	20,29	250	3500	42	88,2							
20A(C)7X586B	7	9,66	22,54	250	3500	42,5	89,3							
20A(C)8,2X586B	8,2	11,32	26,40	250	3500	43,5	91,1							
20A(C)10X586B	10	13,95	32,55	250	3500	45	94,1							
20A(C)11X586B	11,3	15,76	36,78	250	3500	46	96,2							
20A(C)12X586B	12	16,92	39,48	250	3500	46,6	97,5							
20A(C)14X586B	14	19,95	46,55	250	3500	48	100,6							
20A(C)15X586B	15	21,60	36,00	250	2500	49	102,1							
20A(C)16X586B	16	23,04	38,40	250	2500	50	103,8							
20A(C)17,3X586B	17,3	24,91	41,52	230	2500	50,8	105,8							
20A(C)19X586B	19	27,36	45,60	200	2500	52	108,7							
20A(C)22X586B	22	31,68	42,24	180	2000	55	113,7							
20A(C)25X586B	25	36,00	48,00	160	2000	57,2	118,5							