



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension												
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet							
								M	G	U	M	G	U					
20A(C)4,5Y566D...	4,5	6,14	14,33	250	3500	41,8	85	M20x1,5	G1/2	1 1/16"-12UNF	M16x1,5	G1/2	7/8"-14UNF					
20A(C)6,3Y566D...	6,3	8,69	20,29	250	3500	43	88											
20A(C)8,2Y566D...	8,2	11,32	26,40	250	3500	45,1	90,9											
20A(C)10Y566D...	10	13,95	32,55	250	3500	49,5	94		G3/4									
20A(C)11Y566D...	11,3	15,76	36,78	250	3500	49,5	96											
20A(C)12Y566D...	12	16,92	39,48	250	3500	49,5	97,3		G1/2									
20A(C)14Y566D...	14	19,95	46,55	250	3500	49,5	100,4											
20A(C)15Y566D...	15	21,60	36,00	250	2500	49,5	102		M20X1,5									
20A(C)16Y566D...	16	23,04	38,40	250	2500	49,5	103,5											
20A(C)19Y566D...	19	27,36	45,60	200	2500	49,5	108,5		G1/2									
20A(C)22Y566D...	22	31,68	42,24	180	2000	57	113,5											
20A(C)25Y566D...	25	36,00	48,00	160	2000	59,2	118,4											