



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension								
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet			
								E	d	F	E	d	F	
30A(C)20X263H	20	28,2	56,4	200	3000	95,1	152,3	40	M8	19	40	M8	19	
30A(C)22,2X263H	22,5	31,7	63,5	200	3000	96,8	155,4							
30A(C)25X263H	25	35,3	70,5	200	3000	97,4	156,8							
30A(C)28X263H	28	39,5	79,0	200	3000	99,1	160,2							
30A(C)32X263	32	45,1	75,2	200	2500	101,0	163,8							
30A(C)32X263H	32	45,1	90,2	200	3000	105,5	172,8	51	M10	27	40	M8	19	
30A(C)36X263	36	50,8	84,6	190	2500	102,7	166,9							
30A(C)36X263H	36	51,3	95,8	190	2800	107,2	175,9							
30A(C)42X263	42	59,9	91,8	190	2300	105,3	172,5							
30A(C)42X263H	42	59,9	99,8	190	2500	109,8	181,5							
30A(C)46X263H	46	65,6	100,5	175	2300	111,7	186,3	51	M10	27	40	M8	19	
30A(C)50X263H	50	71,3	99,8	175	2100	113,5	188,9							
30A(C)55X263H	55	78,4	91,4	175	1750	115,7	193,4							
30A(C)60X263H	60	85,5	99,8	160	1750	118,0	197,9							